

SECTION 102800 - TOILET, BATH, AND LAUNDRY ACCESSORIES

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
1. Public and private-use washroom accessories.
 2. Underlavatory guards.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.

1.3 CLOSEOUT SUBMITTALS

- A. Maintenance data.

PART 2 - PRODUCTS

2.1 PUBLIC AND PRIVATE-USE WASHROOM ACCESSORIES

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
1. Parker/Nutone, Inc.
 2. American Specialties, Inc.; ASI Group.
 3. Bobrick Washroom Equipment, Inc.
 4. Bradley Corporation.
 5. Other as listed below.
- B. Toilet Tissue Dispenser:
1. Basis-of-Design Product: Bobrick #2730.
 2. Mounting: Surface mounted.
 3. Material and Finish: Stainless steel, No. 4 finish (satin).
- C. Paper Towel Holder:
1. Basis-of-Design Product: Rubbermaid 2361-RD-WHT Paper Towel Holder.
 2. Description: Plastic paper towel holder with folding arms.
 3. Mounting: Surface.
 4. Minimum Towel-Dispenser Capacity: One roll of residential kitchen paper towels.

D. Liquid-Soap Dispenser:

1. Basis-of-Design Product: Bobrick #4112.
2. Description: Designed for dispensing soap in liquid or lotion form.
3. Mounting: Horizontally oriented, surface mounted.
4. Capacity: 40 oz.minimum.
5. Materials: Stainless Steel, No. 4 finish (satin) body and black molded plastic push button.
6. Lockset: Tumbler type.
7. Refill Indicator: Window type.

E. Grab Bar:

1. Mounting: Flanges with concealed fasteners.
2. Material: Stainless steel, 0.05 inch thick.
 - a. Finish: Smooth, No. 4 finish (satin).
3. Outside Diameter: 1-1/2 inches
4. Configuration and Length: As indicated on Drawings.

F. Mirror Unit:

1. Frame: Stainless-steel channel.
 - a. Corners: Manufacturer's standard.
 - b. Size: As indicated on drawings.
2. Hangers: Produce rigid, tamper- and theft-resistant installation, using method indicated below.
 - a. Wall bracket of galvanized steel, equipped with concealed locking devices requiring a special tool to remove.

2.2 UNDERLAVATORY GUARDS

A. Underlavatory Guard:

1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Plumberex Specialty Products, Inc.
 - b. Truebro by IPS Corporation.
2. Description: Insulating pipe covering for supply and drain piping assemblies that prevents direct contact with and burns from piping; allow service access without removing coverings.
3. Material and Finish: Antimicrobial, molded plastic, white.

2.3 FABRICATION

- A. Keys: Provide universal keys for internal access to accessories for servicing and resupplying. Provide minimum of six keys to Owner's representative.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Install accessories according to manufacturers' written instructions, using fasteners appropriate to substrate indicated and recommended by unit manufacturer. Install units level, plumb, and firmly anchored in locations and at heights indicated.
- B. Grab Bars: Install to withstand a downward load of at least 250 lbf, when tested according to ASTM F 446.

END OF SECTION 102800

NO PRINTING THIS PAGE