



ROOF FRAMING PLAN SCALE: 1/8" = 1'-0'

NOTES 1) TOP OF STEEL (DECK BEARING) ELEVATION, VARIES SEE PLAN.

2) - DI INDICATES SPAN OF 1 1/2" 22 Ga. (GALV.) METAL ROOF DECK (TYPE 'B').

3) PROVIDE FLEXIBLE MOMENT CONNECTION FOR LATERAL LOADS, SEE TYPICAL DETAIL ON 54.0.

4) COORDINATE ALL EDGE OF DECK DIMENSIONS AT SHAFT OPENINGS, BUILDING PERIMETER, ETC,. WITH THE ARCHITECTURAL DRAWINGS.

5) SEE ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS. DIMENSIONS SHOWN ON THIS DRAWING ARE FOR CONVENIENCE ONLY AND MUST BE CHECKED WITH ARCHITECTURAL DRAWINGS FOR ACCURACY. DIMENSIONS ON ARCHITECTURAL DRAWINGS GOVERN.



1) COORDINATE TOP OF STEEL ELEVATION W/ ARCHITECTURAL DRAWINGS.

DETAIL ON S4.0.

2) $-D_{\mu}^{1}$ indicates span of 1 1/2" 22 Ga. (GALV.) Metal roof deck (type 'b'). 3) PROVIDE FLEXIBLE MOMENT CONNECTION FOR LATERAL LOADS, SEE TYPICAL

4) ALL BEAM/GIRDER CONNECTIONS NOT CONNECTED TO COLUMNS SHALL BE DESIGNED FOR A MINIMUM UNFACTORED VERTICAL REACTION OF 20 kips, UNLESS NOTED GREATER. CONNECTIONS TO COLUMNS TO BE PER GENERAL NOTES. ALL REACTIONS SHOWN ON PLAN ARE SERVICE LOADS.

5) COORDINATE ALL EDGE OF SLAB DIMENSIONS AT SHAFT OPENINGS, BUILDING PERIMETER, ETC, WITH THE ARCHITECTURAL DRAWINGS.

6) SEE ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS. DIMENSIONS SHOWN ON THIS DRAWING ARE FOR CONVENIENCE ONLY AND MUST BE CHECKED WITH ARCHITECTURAL DRAWINGS FOR ACCURACY. DIMENSIONS ON ARCHITECTURAL DRAWINGS GOVERN.



CUPULA FRAMING PLAN

SCALE: 1/0' = 1'-0'NOTES: 1) COORDINATE TOP OF STEEL ELEVATION W/ ARCHITECTURAL DRAWINGS. 2) $_D1_{_}$ indicates span of 1 1/2" 22 Ga. (GALV.) metal roof deck (type 'b').

3) PROVIDE FLEXIBLE MOMENT CONNECTION FOR LATERAL LOADS, SEE TYPICAL DETAIL ON S4.0.

4) ALL BEAM/GIRDER CONNECTIONS NOT CONNECTED TO COLUMNS SHALL BE DESIGNED FOR A MINIMUM UNFACTORED VERTICAL REACTION OF 20 kips, UNLESS NOTED GREATER. CONNECTIONS TO COLUMNS TO BE PER GENERAL NOTES. ALL REACTIONS SHOWN ON PLAN ARE SERVICE LOADS.

5) COORDINATE ALL EDGE OF SLAB DIMENSIONS AT SHAFT OPENINGS, BUILDING PERIMETER, ETC,. WITH THE ARCHITECTURAL DRAWINGS.

6) SEE ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS. DIMENSIONS SHOWN ON THIS DRAWING ARE FOR CONVENIENCE ONLY AND MUST BE CHECKED WITH ARCHITECTURAL DRAWINGS FOR ACCURACY. DIMENSIONS ON ARCHITECTURAL DRAWINGS GOVERN.

7) "BEND POINT" INDICATES LOCATION OF FULL-PENETRATION WELD AT BENT BEAM.



1) COORDINATE TOP OF STEEL ELEVATION w/ ARCHITECTURAL DRAWINGS. 2) $-D_{\perp}^{D_{\perp}}$ indicates span of 1 1/2" 22 Ga. (GALV.) Metal roof deck (type 'b'). 3) PROVIDE FLEXIBLE MOMENT CONNECTION FOR LATERAL LOADS, SEE TYPICAL DETAIL ON S4.0.

REACTIONS SHOWN ON PLAN ARE SERVICE LOADS.

5) COORDINATE ALL EDGE OF SLAB DIMENSIONS AT SHAFT OPENINGS, BUILDING PERIMETER, ETC, WITH THE ARCHITECTURAL DRAWINGS.

DRAWINGS GOVERN.

7) "BEND POINT" INDICATES LOCATION OF FULL-PENETRATION WELD AT BENT BEAM.

4) ALL BEAM/GIRDER CONNECTIONS NOT CONNECTED TO COLUMNS SHALL BE DESIGNED FOR A MINIMUM UNFACTORED VERTICAL REACTION OF 20 kips, UNLESS NOTED GREATER. CONNECTIONS TO COLUMNS TO BE PER GENERAL NOTES. ALL

6) SEE ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS. DIMENSIONS SHOWN ON THIS DRAWING ARE FOR CONVENIENCE ONLY AND MUST BE CHECKED WITH ARCHITECTURAL DRAWINGS FOR ACCURACY. DIMENSIONS ON ARCHITECTURAL



2/1/2019 9:22:05 PM