




(1) PER ASC7 CASE B LOADING. CASE B LOADING = (CASE A LOADING) X (1.67). THE PRESSURES HAVE BEEN MULTIPLIED BY 0.6 (ASD LOAD FACTOR).  
 (2) 0.7V PER ASC7-16 ASD EQUATIONS.  
 (3) COLUMN MAY BE SPICED WITH A PREQUALIFIED CJP WELD.  
 (\*) MAY NEED LONGER BOLTS FOR CLAMP ATTACHMENTS.

REV	DATE	REVISED MARKING SURFACE NOTE UNDER FRONT VIEW.		BY
01	15 SEP 21			SAC
<p>THE CONCEPTS EXPRESSED AND DETAILS 3/4" OR IN THE DRAWINGS ARE CONSIDERED AND PROBABLY HAVE NO EFFECT REPRODUCED BY ANY MEANS WITHOUT THE EXPRESS WRITTEN CONSENT OF MATTHEWS, INC. OR ITS SUBSIDIARIES OR AFFILIATES.</p> <p>Copyright 2020 MATTHEWS, INC. (USA)</p>		<p>THIS AREA PROVIDES THE USER WITH THE INFORMATION REQUIRED TO PRODUCE THE PART.</p> 		
<p><b>DATACONCEPTS</b></p>				
PROJECT	2019 CBC DSA PRE-CHECK DRAWING			
DATE	2019 CBC DSA PRE-CHECK DRAWING			
SCALE	1" = 1" 1/2" COLUMN STRUT TO OTHER FOUNDATIONS			
DATE	11 MAY 20			
SCALE	1/8" = 1" 1/2" INCHES (MILLIMETERS)			
DESIGN	SEASTMA JOB NO. FUNC. TYPE: SIZE			
ORIGIN	SEASTMA 2236 F 10 D			
				4682222